

# DIGITUS USB-C silicone connection cable, 1m, black

AK-300341-010-S  
EAN 4016032495796



## USB-C Silicone charging cable, USB-C - USB-C 1m, USB 2.0, 60W, black

Reliable and easy connection to your USB-C devices with your PC thanks to the soft and flexible silicone cable. Data transfer rate of 480 Mbits/s for synchronization, data transfer and a power delivery specification of 60W for charging.

### Fast charging and synchronization with the high-quality and soft silicone connection cable

- Supports data transfer rates of 480 Mbit/s
- Backwards compatible with USB 2.0 and USB 1.1
- Supports the USB power delivery function with 20V, 3A and 60W

- Durable cable with a service life of up to 25,000 bends (based on internal tests)
- Type C plug can be used on both sides

### Attributes

- AWG: 24
- Color cable: black
- Connector 1: USB C, plug
- Connector 2: USB C, plug
- Connector surface: nickel-plated
- Hoods: molded
- Wire material: CU
- Length: 1 m
- Shielding: single shielding

## Logistics

|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³       |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------|
| Packaging Unit Carton        | 200          | 7.90        | 21.00      | 32.00      | 50.00       | 33,600.00 |
| Packaging Unit Inside        | 10           | 0.40        | 3.60       | 24.00      | 30.00       | 2,592.00  |
| Packaging Unit Single        | 1            | 0.04        | 1.00       | 21.00      | 11.50       | 240.29    |
| Net single without Packaging | 1            | 0.03        | 0.90       | 12.00      | 10.00       | 0.00      |

## More images:





#### Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

#### EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)