

Data sheet: die set 624 1016

Crimping cavity	1	2	3
Cable cross section	AWG 28 - AWG 26	AWG 18 - AWG 16	AWG 22 - AWG 20
Crimping height	0,80 mm	1,16 mm	0,94 mm
Height tolerances	± 0,05 mm	± 0,05 mm	± 0,05 mm
Step	-	-	-
Wire crimping width	1,32 mm	1,65 mm	1,57 mm
Width tolerance	± 0,10 mm	± 0,10 mm	± 0,10 mm
Insulation crimping height	1,56 mm	2,87 mm	2,69 mm
Insulation crimping width	1,65 mm	2,44 mm	2,31 mm
Seal	-	-	-
Special aspects	-	-	-
PN Strip	Würth Elektronik 4.20 Female Crimp Contact 649 001 137 22, 649 002 137 22, 649 006 137 22, 649 007 137 22 Würth Elektronik 4.20 Male Crimp Contact 649 000 137 22, 649 003 137 22, 649 004 137 22, 649 009 137 22	Tyco Electronics Terminal Pin VAL-U-LOK 794955-1 Würth Elektronik 4.20 Female Crimp Contact 649 005 137 22 Würth Elektronik 4.20 Male Crimp Contact 649 008 137 22	Tyco Electronics Terminal Pin VAL-U-LOK 794955-1 Würth Elektronik 4.20 Female Crimp Contact 649 001 137 22, 649 006 137 22 Würth Elektronik 4.20 Male Crimp Contact 649 003 137 22, 649 009 137 22
PN Loose	Würth Elektronik 4.20 Female Crimp Contact 649 001 137 22 DEC, 649 002 137 22 DEC, 649 006 137 22 DEC, 649 007 137 22 DEC Würth Elektronik 4.20 Male Crimp Contact 649 000 137 22 DEC, 649 003 137 22 DEC, 649 004 137 22 DEC, 649 009 137 22 DEC	Würth Elektronik 4.20 Female Crimp Contact 649 005 137 22 DEC Würth Elektronik 4.20 Male Crimp Contact 649 008 137 22 DEC	Würth Elektronik 4.20 Female Crimp Contact 649 001 137 22 DEC, 649 006 137 22 DEC Würth Elektronik 4.20 Male Crimp Contact 649 003 137 22 DEC, 649 009 137 22 DEC

Tools

