



Miniature SOP4-pin type of 60V/350V/400V load voltage

PhotoMOS®
GU SOP 1 Form A
(AQY210S)



RoHS compliant

FEATURES

1. **Controls low-level analog signals**
PhotoMOS feature extremely low closed-circuit offset voltage to enable control of low-level analog signals without distortion.
2. **Small SOP4-Pin package**
The device comes in a miniature SOP4-pin type measuring (W)4.3 × (L)4.4 × (H)2.1 mm (W).169 × (L).173 × (H).083 inch
3. **Low-level off state leakage current of max. 1 µA**
4. **Load voltage 60V, 350V and 400V types available**

TYPICAL APPLICATIONS

- Telecommunication (PC, electronic notepad)
- Measuring and testing equipment
- Factory automation equipment
- Security equipment
- Computers
- Industrial robots

TYPES

	Output rating*		Package	Part No.			Packing quantity		
	Load voltage	Load current		Tape and reel packing style		Tube	Tape and reel		
				Tube packing style	Picked from the 1/2-pin side				
AC/DC dual use	60V	500mA	SOP4-pin	AQY212S	AQY212SX	AQY212SZ	1 tube contains: 100 pcs. 1 batch contains: 2,000 pcs.	1,000 pcs.	
	350V	120mA		AQY210S	AQY210SX	AQY210SZ			
	400V	100mA		AQY214S	AQY214SX	AQY214SZ			

* Indicate the peak AC and DC values.

Note: For space reasons, the three initial letters of the part number "AQY", the surface mount terminal indicator "S" and the packing style indicator "X" or "Z" are not marked on the device. (Ex. the label for product number AQY210SX is 210.)

RATING

1. Absolute maximum ratings (Ambient temperature: 25°C 77°F)


Item		Symbol	AQY212S	AQY210S	AQY214S	Remarks
Input	LED forward current	I _F		50 mA		
	LED reverse voltage	V _R		5 V		
	Peak forward current	I _{FP}		1 A		f = 100 Hz, Duty factor = 0.1%
	Power dissipation	P _{Dn}		75 mW		
Output	Load voltage (peak AC)	V _L	60 V	350 V	400 V	
	Continuous load current	I _L	0.5 A	0.12 A	0.1 A	Peak AC, DC
	Peak load current	I _{peak}	1.5 A	0.3 A	0.24 A	100ms (1 shot), V _L = DC
	Power dissipation	P _{out}		300 mW		
Total power dissipation		P _T		350 mW		
I/O isolation voltage		V _{Iso}		1,500 Vrms		
Ambient temperature	Operating	T _{opr}	−40 to +85°C −40 to +185°F		(Non-icing at low temperatures)	
	Storage	T _{sig}	−40 to +100°C −40 to +212°F			

GU SOP 1 Form A (AQY21OS)

2. Electrical characteristics (Ambient temperature: 25°C 77°F)

Item			Symbol	AQY212S	AQY210S	AQY214S	Condition		
Input	LED operate current		I_{Fon}	0.9 mA			$I_L = \text{Max.}$		
	Maximum			3 mA					
Output	LED turn off current		I_{Foff}	0.4 mA			$I_F = \text{Max.}$		
	Typical			0.85 mA					
Transfer characteristics	LED dropout voltage		V_F	1.25 V (1.14 V at $I_F = 5 \text{ mA}$)			$I_F = 50 \text{ mA}$		
	Maximum			1.5 V					
Output	On resistance		R_{on}	0.83 Ω	17 Ω	25 Ω	$I_F = 5 \text{ mA}$ $I_L = \text{Max.}$ Within 1 s		
	Maximum			2.5 Ω	25 Ω	35 Ω			
Off state leakage current			I_{Leak}	1 μA			$I_F = 0 \text{ mA}$ $V_L = \text{Max.}$		
Transfer characteristics	Turn on time*		T_{on}	0.65 ms	0.23 ms	0.21 ms	$I_F = 5 \text{ mA}$ $I_L = \text{Max.}$		
	Maximum			2 ms	0.5 ms	0.5 ms			
Transfer characteristics	Turn off time*		T_{off}	0.08 ms	0.04 ms		$I_F = 5 \text{ mA}$ $I_L = \text{Max.}$		
	Maximum			0.2 ms					
I/O capacitance			C_{iso}	1.5 pF			$f = 1 \text{ MHz}$ $V_B = 0 \text{ V}$		
Initial I/O isolation resistance			R_{iso}	1,000 MΩ			500 V DC		

*Turn on/Turn off time



3. Recommended operating conditions (Ambient temperature: 25°C 77°F)

Please use under recommended operating conditions to obtain expected characteristics.

Item		Symbol	Min.	Max.	Unit
LED current		I_F	5	30	mA
AQY212S	Load voltage (Peak AC)	V_L	—	48	V
	Continuous load current	I_L	—	0.5	A
AQY210S	Load voltage (Peak AC)	V_L	—	280	V
	Continuous load current	I_L	—	0.12	A
AQY214S	Load voltage (Peak AC)	V_L	—	320	V
	Continuous load current	I_L	—	0.1	A


■ These products are not designed for automotive use.

If you are considering to use these products for automotive applications, please contact your local Panasonic Corporation technical representative.

REFERENCE DATA


1. Load current vs. ambient temperature characteristics

Allowable ambient temperature: -40 to +85°C
-40 to +185°F




2. On resistance vs. ambient temperature characteristics

Measured portion: between terminals 3 and 4;
LED current: 5 mA; Load voltage: Max. (DC);
Continuous load current: Max. (DC)




3. Turn on time vs. ambient temperature characteristics

LED current: 5 mA; Load voltage: Max. (DC);
Continuous load current: Max. (DC)




4. Turn off time vs. ambient temperature characteristics


LED current: 5 mA; Load voltage: Max. (DC); Continuous load current: Max. (DC)

**7. LED dropout voltage vs. ambient temperature characteristics**


Sample: All types; LED current: 5 to 50 mA

**9. Off state leakage current vs. load voltage characteristics**


Measured portion: between terminals 3 and 4; Ambient temperature: 25°C 77°F

**12. Output capacitance vs. applied voltage characteristics**


Measured portion: between terminals 3 and 4; Frequency: 1 MHz; Ambient temperature: 25°C 77°F

**5. LED operate current vs. ambient temperature characteristics**


Sample: All types; Load voltage: Max. (DC); Continuous load current: Max. (DC)

**6. LED turn off current vs. ambient temperature characteristics**


Sample: All types; Load voltage: Max. (DC); Continuous load current: Max. (DC)

**8-(1). Current vs. voltage characteristics of output at MOS portion**


Measured portion: between terminals 3 and 4; Ambient temperature: 25°C 77°F

**8-(2). Current vs. voltage characteristics of output at MOS portion**


Measured portion: between terminals 3 and 4; Ambient temperature: 25°C 77°F

**10. Turn on time vs. LED forward current characteristics**

Measured portion: between terminals 3 and 4; Load voltage: Max. (DC); Continuous load current: Max. (DC); Ambient temperature: 25°C 77°F

**11. Turn off time vs. LED forward current characteristics**

Measured portion: between terminals 3 and 4; Load voltage: Max. (DC); Continuous load current: Max. (DC); Ambient temperature: 25°C 77°F



"PhotoMOS®", "PhotoMOS" and "PHOTOMOS" are registered trademarks of Panasonic Corporation.

*Recognized in Japan, the United States, all member states of European Union and other countries.

Please contact

Panasonic Corporation

Electromechanical Control Business Division

■ 1006, Oaza Kadoma, Kadomashi, Osaka 571-8506, Japan
industrial.panasonic.com/ac/e/

Panasonic®

©Panasonic Corporation 2017