

REC5K-RW series

5W / Isolated Single Output / 4:1 Input

FEATURES

- 4kVDC/1sec isolation
- Industry standard 5W DIP24 package
- Low ripple and noise
- Derates to 110°C ambient temperature
- Wide 4:1 input
- ON/OFF control pin, UVLO, SCP
- 0% minimum load



Dimensions (LxWxH): 32.1 x 20.6 x 10.2mm (1.26 x 0.81 x 0.40inch)
12.0g (0.03 lbs)

APPLICATIONS



SAFETY & EMC



DESCRIPTION

This series offers 4kVDC/1sec isolation and internal filtering to reduce noise, making it ideal for both industrial and other sophisticated high end applications. The compact DIP24 non-conductive plastic package ensures high power density without compromising performance, operating with derating up to 110°C. Short circuit protection, undervoltage lockout, and remote on/off control is standard, and the converter is certified according to UL/IEC/EN62368-1.

SELECTION GUIDE

Part Number	Input Voltage Range [VDC]	Output Voltage [VDC]	Output Current [mA]	Efficiency typ. [%]	max. Capacitive Load [µF]
REC5K-2405SRW/H4/A	9 - 36	5	1000	78	3000

Note1: Efficiency is tested at nominal input and full load at +25°C ambient

Note2: Max Cap Load is tested at nominal input and full resistive load




REC5K-RW series

5W / Isolated Single Output / 4:1 Input

BASIC CHARACTERISTICS (measured @ $T_{AMB} = 25^{\circ}C$, nom. V_{IN} , full load and after warm-up unless otherwise stated)

Parameter	Condition	Min.	Typ.	Max.
Input Voltage Range	nom. $V_{IN} = 24VDC$	9VDC		36VDC
Input Under Voltage Lockout (UVLO)	DC-DC ON	8.2VDC		8.8VDC
	DC-DC OFF	5.4VDC		6.0VDC
Input Current		240mA		270mA
Quiescent Current				20mA
Minimum Load		0%		
Startup time				50ms
ON/OFF CTRL	DC-DC ON	Open or $V_{CTRL} > 1.5VDC$		
	DC-DC OFF	Short to $-V_{IN}$ or $< 1.5VDC$		
Input Current on CTRL Pin	DC-DC ON			1mA
Standby Current			3mA	6mA
Internal Operating Frequency				400kHz
Output Ripple and Noise ⁽³⁾	20MHz BW			80mVp-p


Note3: Measurements are made with a 10µF MLCC across output. (low ESR)



REGULATIONS

Parameter	Condition	Value
Output Accuracy		±2.5% typ.
Line Regulation	low line to high line, full load	±2.0% max.
Load Regulation ⁽⁴⁾	10% to 100% load	2.0% max.
Transient Response Recovery Time	25% load step change (75% - 100%)	500µs

Note4: Operation below 10% load will not harm the converter, but specifications may not be met



PROTECTIONS

Parameter	Condition	Value
Short Circuit Protection (SCP)		hiccup mode, auto recovery
Short Circuit Input Current	nom. V_{in} = 24VDC	120mA max.
Isolation Voltage ⁽⁵⁾	1 second	4kVDC
	1 minute	2kVAC/50Hz
Isolation Resistance	I/P to O/P, V_{ISO} = 500VDC	1GΩ min.
Isolation Capacitance	I/P to O/P, 100kHz/0.1V	50pF max.
Insulation Grade	according to 62368-1	functional


Note5: For repeat Hi-Pot testing, reduce the time and/or the test voltage

Note6: Refer to local safety regulations if input over-current protections is also required. Recommended fuse: slow blow type

ENVIRONMENTAL

Parameter	Condition	Value	
Operating Temperature Range	with derating refer to „Derating Graph“	-40°C to +100°C	
Maximum Case Temperature		+110°C	
Operating Altitude		5000m	
Operating Humidity	non-condensing	95% RH max.	
Polution Degree		PD2	
MTBF	according to MIL-HDBK-217F, G.B., +25°C	T_{AMB} = +25°C	1741 x 10 ³ hours
		T_{AMB} = +65°C	661 x 10 ³ hours


ENVIRONMENTAL



SAFETY AND CERTIFICATIONS

Certificate Type (Safety)	Report Number	Standard
Audio/Video, information and communication technology equipment - Part1: Safety requirements 3rd Edition	E491408-A6026-UL	UL62368-1:2019 3rd Edition
		CAN/CSA-C22.2 No. 62368-1-19 3rd Edition
Audio/Video, information and communication technology equipment - Part1: Safety requirements 3rd Edition (CB Scheme)	085-220181101-000	IEC62368-1:2018 3rd Edition
		EN IEC 62368-1:2020+A11:2020
RoHS2		RoHS 2011/65/EU + AM2015/863
EMC Compliance	Condition	Standard /Criterion
Electromagnetic Compatibility of Multimedia Equipment - Emission Requirements	with external filter	EN55032, Class B

EMC Filtering Suggestions according to EN55032



Component List Class B

L1	C1	C2/C3
RLS-226	22μF	1nF/4kVDC



DIMENSION & PHYSICAL CHARACTERISTICS

Parameter	Type	Value
Material	case	black plastic, (UL94 V-0)
	potting	PU, (UL94 V-0)
	PCB	FR4, (UL94 V-0)
Dimension (LxWxH)		32.1 x 20.6 x 10.2mm
		1.26 x 0.81 x 0.40inch
Weight		12g typ.
		0.03 lbs

REC5K-RW series

5W / Isolated Single Output / 4:1 Input

Dimension Drawing (mm)



Pinning Information

Pin #	Function
1	CTRL
2, 3	-Vin
9	NC
11	NC
14	+Vout
16	-Vout
22, 23	+Vin

NC= No Connection

Tolerances:
 x.x= ±0.5mm
 x.xx= ±0.25mm

PACKAGING INFORMATION

Parameter	Type	Value
Packaging Dimension (LxWxH)	tube	512.9 x 22.2 x 20.9mm
Packaging Quantity		14pcs
Storage Temperature Range		-50°C to +125°C
Storage Humidity	non-condensing	95% RH max.

The product information and specifications may be subject to changes even without prior written notice. The product has been designed for various applications; its suitability lies in the responsibility of each customer. The products are not authorized for use in safety-critical applications without RECOM's explicit written consent. A safety-critical application is an application where a failure may reasonably be expected to endanger or cause loss of life, inflict bodily harm or damage property. The applicant shall indemnify and hold harmless RECOM, its affiliated companies and its representatives against any damage claims in connection with the unauthorized use of RECOM products in such safety-critical applications.