HSF RoHS

SPECIFICATIONS
Rated Current:3.0AMP
Contact Resistance:30mΩ Max
Withstand Voltage:1000V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:-40°c to +105°c

Contact Material:Brass
Contact Plating:Au or Sn Over Ni
Insulator Material:Polyester(UL94V-0)
Max.Processing Temp:
(PBT)245°C±5°C For 5~10 Second







Ordering Information

3511 3 XX A M S XX X N A X

- No.of Pins: NPin, N=21、30、48, 66、96、120
- Contact Type: F=Female
- Contact Plating: G0:Gold Flash; S0:Gold Flash/Tin; S1:3U" Gold/Tin; S2:5U" Gold/Tin; S3:10U" Gold/Tin; S4:15U" Gold/Tin; S5:30U" Gold/Tin
- Material: B=Brass+PBT
- Code Stream



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)

Dimension antitheses list	
ITEM	A
Standard	4.00

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A0	2022.03.20	NEW DRAWING	

OPERATION	
X.X	±0.30
X.XX	±0.20
X.XXX	±0.10
Angle	±3°
DIM	TOL

DRAW	Jelly Feng	2022.03.20
CHECK		
APPROVE		

SCALE	FIT
UNIT	mm
SIZE	A4
SHEET	1/1
PROJ.	

JiLN® 深圳市锦凌电子有限公司
SHENZHEN JINLING ELECTRONICS CO.,LTD
Tel：86-755-27483253 Fax：86-755-2997-5588

PART NO.	35113XXAMSXXXNAX
TITLE:	欧式插座 公座 180° 成品系列图